

JXP(Pads)for:PAD-6



SPECIFICATION SHEET

Part Number	Value(dB)	Insertion Loss@MHz					Total Attenuation(dB)
		5	550	750	860	1000	
<i>Pad-6-00</i>	0.0	0.0	0.0	0.0	0.0	0.0	0.0
<i>Pad-6-01</i>	1.0	1.0	1.0	1.0	1.0	1.0	1.0
<i>Pad-6-02</i>	2.0	2.0	2.0	2.0	2.0	2.0	2.0
<i>Pad-6-03</i>	3.0	3.0	3.0	3.0	3.0	3.0	3.0
<i>Pad-6-04</i>	4.0	4.0	4.0	4.0	4.0	4.0	4.0
<i>Pad-6-05</i>	5.0	5.0	5.0	5.0	5.0	5.0	5.0
<i>Pad-6-06</i>	6.0	6.0	6.0	6.0	6.0	6.0	6.0
<i>Pad-6-07</i>	7.0	7.0	7.0	7.0	7.0	7.0	7.0
<i>Pad-6-08</i>	8.0	8.0	8.0	8.0	8.0	8.0	8.0
<i>Pad-6-09</i>	9.0	9.0	9.0	9.0	9.0	9.0	9.0
<i>Pad-6-10</i>	10.0	10.0	10.0	10.0	10.0	10.0	10.0
<i>Pad-6-11</i>	11.0	11.0	11.0	11.0	11.0	11.0	11.0
<i>Pad-6-12</i>	12.0	12.0	12.0	12.0	12.0	12.0	12.0
<i>Pad-6-13</i>	13.0	13.0	13.0	13.0	13.0	13.0	13.0
<i>Pad-6-14</i>	14.0	14.0	14.0	14.0	14.0	14.0	14.0
<i>Pad-6-15</i>	15.0	15.0	15.0	15.0	15.0	15.0	15.0
<i>Pad-6-16</i>	16.0	16.0	16.0	16.0	16.0	16.0	16.0
<i>Pad-6-17</i>	17.0	17.0	16.9	16.9	16.9	16.9	17.0
<i>Pad-6-18</i>	18.0	18.0	17.9	17.9	17.8	17.7	18.0
<i>Pad-6-19</i>	19.0	18.9	18.9	18.9	18.8	18.6	19.0
<i>Pad-6-20</i>	20.0	19.9	19.9	19.9	19.8	19.6	20.0
<i>Pad-6-75</i>	75ohm	N/A	N/A	N/A	N/A	N/A	N/A

Return Loss I/O: **19dB**.

Passband Flatness:**0.3dB**,Peak to Valley.