


JXP(Pads)for:SPB



SPECIFICATION SHEET

Part Number	Value(dB)	Insertion Loss@MHz					Total Attenuation(dB)
		5	550	750	860	1000	
SPB-00	0.0	0.0	0.0	0.0	0.0	0.0	0.0
SPB-01	1.0	1.0	1.0	1.0	1.0	1.0	1.0
SPB-02	2.0	2.0	2.0	2.0	2.0	2.0	2.0
SPB-03	3.0	3.0	3.0	3.0	3.0	3.0	3.0
SPB-04	4.0	4.0	4.0	4.0	4.0	4.0	4.0
SPB-05	5.0	5.0	5.0	5.0	5.0	5.0	5.0
SPB-06	6.0	6.0	6.0	6.0	6.0	6.0	6.0
SPB-07	7.0	7.0	7.0	7.0	7.0	7.0	7.0
SPB-08	8.0	8.0	8.0	8.0	8.0	8.0	8.0
SPB-09	9.0	9.0	9.0	9.0	9.0	9.0	9.0
SPB-10	10.0	10.0	10.0	10.0	10.0	10.0	10.0
SPB-11	11.0	11.0	11.0	11.0	11.0	11.0	11.0
SPB-12	12.0	12.0	12.0	12.0	12.0	12.0	12.0
SPB-13	13.0	13.0	13.0	13.0	13.0	13.0	13.0
SPB-14	14.0	14.0	14.0	14.0	14.0	14.0	14.0
SPB-15	15.0	15.0	15.0	15.0	15.0	15.0	15.0
SPB-16	16.0	16.0	16.0	16.0	16.0	16.0	16.0
SPB-17	17.0	17.0	16.9	16.9	16.9	16.9	17.0
SPB-18	18.0	18.0	17.9	17.9	17.8	17.7	18.0
SPB-19	19.0	18.9	18.9	18.9	18.8	18.6	19.0
SPB-20	20.0	19.9	19.9	19.9	19.8	19.6	20.0
SPB-75	75ohm	N/A	N/A	N/A	N/A	N/A	N/A

Return Loss I/O: **19dB**.

Passband Flatness:**0.3dB**,Peak to Valley.